

RoHS Compliant

REVISIONS			
REV.	DESCRIPTION	DATE	DESIGN



Specifications

Current Rating: 7.0Amp
 Insulation Resistance: 100MΩ Min.
 Dielectric Withstanding: 500V AC
 Contact Resistance: 30MΩ Max.
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Phosphor Bronze
 Insulation Material: Polyester, UL 94V-0
 Nylon 9T
 All materials must be ROHS materials




Recommended P.C.Board
 Hole Layout
 (Tolerance: ±0.05)



PART NO. INFORMATION

BH250-XX F X C 5 T - 002

NO.OF PINS PER ROW: 03-11
 GENDER: F: FEMALE, M: MALE
 CONTACT PLATED: 1:TIN, 2: GOLD FLASH
 PACKAGE: T: TUBE
 HOUSING COLOR: 5: BLACK
 HOUSING MATERIAL: C: PA9T



Bestcreate Technology Limited

TOLERANCES UNLESS OTHERWISE SPECIFIED:

X.	± 0.30	X.'	± 5'
.X	± 0.25	.X'	± 3'
.XX	± 0.15	.XX'	± 2'

Website: www.bsc-elec.com
 Email: bestcreate@bsc-elec.com

DESIGN: I.L DATE: 2017.3.1

CHECKED: C.W DATE: 2017.3.1

APPROVED: C.W DATE: 2017.3.1

TITLE: 2.5MM BATTERY HOLDER FEMALE SMT TYPE

MATERILA: PART NO: BH250-XXFXC5T-002 SIZE: A4

FINSH: DWG NO: BH250-XXFXC5T-002

REV: A	UNIT: mm	SCALE: 1=1	QUALITY SYMBOLS
--------	----------	------------	-----------------